



COMPLETE ENVIRONMENTAL SOLUTIONS



Air, Sound, Water, Soil Pollution Monitoring Instruments Manufacturing, Sales, Servicing & Calibration

870FF, BLOCK-A, AFFORDABLE HOUSE, MU-II, GREATER NOIDA, GAUTAM BUDDH NAGAR-201310, U.P., INDIA

+91-7840088951, +91-8130667557, +91-8585922660

cesindia@ymail.com,

cesindia1@gmail.com,

www.cesindia.co.in

GSTIN NO: 09EPS8978Q1ZY

PAN NO : EPS8978Q

PRODUCT LIST

AIR POLLUTION MONITORING INSTRUMENTS

- RESPIRABLE DUST SAMPLER (PM10)
- FINE PARTICULATE SAMPLER (PM2.5)
- COMBO SAMPLER (PM10+PM2.5)
- STACK SAMPLER
- HANDY DUST SAMPLER
- PERSONAL SAMPLER
- BENZENE SAMPLER
- LOW VOLUME SAMPLER
- GASEOUS POLLUTANT SAMPLER
- THERMO ELECTRICALLY COOLED GASEOUS ATTACHMENT
- THERMO ELECTRICALLY COOLED GASEOUS ATTACHMENT
- SOUND LEVEL METER
- WEATHER MONITOR
- LUX METER • VIBRATION METER
- TOP LOADING CALIBRATOR
- FLOW CALIBRATOR
- TIME CALIBRATOR
- SOUND LEVEL CALIBRATOR

LAB INSTRUMENTS

- BIO SAFETY CABINET
- FUME HOOD
- BOD INCUBATOR
- COD DIGESTOR
- AUTO CLAVE
- BIOLOGICAL INCUBATOR
- HOT AIR OVEN • WATER BATH
- HUMIDITY CHAMBER
- HOT PLATE
- DISTILLATION UNIT
- HEATING MENTLE
- KJELDAL ASSEMBLY
- DEEP FRIZZER
- PH METER

RTD CALIBRATOR DT – CC - 02



Description: -

- Accuracy $\pm 0.02\%$
- Standard Accessories: Test Lead, Hostler, Manual
- Product Code: CC-02
- Model No: HTC-Q2
- Dimension: 190(H) x 89(W) x 42(D)mm
- Warranty: As Per Manufacturer Terms and Condition

Product Specification

OHM Measurement:

| Output | Input Accuracy $\pm\Omega$ | |
|----------------------------------|----------------------------|-------------------|
| RANGE | 4 WRITE | 2 WRITE & 3 WRITE |
| 0.00 Ω -400.00 Ω | 0.1 | 0.15 Ω |
| 400.0 Ω -1500.0 Ω | 0.5 | 1 Ω |
| 1500.0 Ω -3200.0 Ω | 1.0 | 1.5 |

OHM Simulate:

| RANGE | Output Accuracy $\pm\Omega$ | Allow Excitation(mA) |
|----------------------------------|-----------------------------|----------------------|
| 0.00 Ω -400.00 Ω | 0.1 | 0.1~3.0 |
| 400.0 Ω -1500.0 Ω | 0.5 | 0.05~0.8 |
| 1500.0 Ω -3200.0 Ω | 1.0 | 0.05~0.4 |

- TDS METER
- CONDUCTIVITY METER
- SPECTROPHOTOMETER
- WEIGHING BALANCE
- MOISTURE ANALYZER
- DIGITAL ULTRASONIC CLEANER
- DO METER
- GRADIENT THERMAL CYCLE/PCR
- ICE FLAKER
- ICE MAKER
- PROBE SONICATOR
- DIGITAL VISCOMETER
- DIGITAL PRESSURE INDICATOR
- ION SELECTIVE ELECTRODES
- POLARIMETERS
- VISCOMETERS
- PROBE SONICATOR-TOUCHSCREEN
- ION WITH PH METER-5 POINTS
- PH ELECTRODES
- MULTI PARAMETER / DO METER
- REFRACTO METERS
- GRADIENT THERMAL CYCLER
- ULTRASONIC CLEANERS
- CERAMIC HOTPLATE
- MAGNETIC STIRRER
- DIGITAL PIPETTES
- REFRIGERATED CIRCULATING BATH
- DIGITAL WATER BATH
- ANALOG MULTIMETER
- DIGITAL MULTIMETER
- BENCH TYPE TRUE RMS DIGITAL MULTIMETER
- AC CLAMP METER
- AC/DC CLAMP METER
- POWER CLAMP METER
- AC LEAKAGE CURRENT TESTER
- EARTH LEAKAGE
- INSULATION RESISTANCE TESTER
- PHASE ROTATION METER
- VOLTAGE DETECTOR
- DIGITAL CAPACITANCE METER
- DIGITAL LCR METER
- DIGITAL MILLIOHM METER
- LUX METER

RTD Specification:

| RTD TYPE | Range(°f) | Accuracy(°c) | | | Allowable Excitation(mA) |
|----------------|-----------------------------|--------------|-------|--------|--------------------------|
| | | INPUT | | OUTPUT | |
| | | 4w | 2w/3w | | |
| Pt1093850 | -200.0~800.0(-328.0~1472.0) | 1.5 | 1.5 | 1.5 | 0.1~3.0 |
| PT50(385) | -200.0~800.0(-328.0~1472.0) | 0.3 | 0.5 | 0.5 | 0.1~3.0 |
| PT100(385) | -200.0~800.0(-328.0~1472.0) | 0.3 | 0.4 | 0.4 | 0.1~0.3 |
| Pt200(385) | -200.0~630.0(-328.0~1166.0) | 0.2 | 0.4 | 0.4 | 0.1~0.3 |
| Pt500(385) | -200.0~630.0(-328.0~1166.0) | 0.2 | 0.4 | 0.4 | 0.05~0.8 |
| Pt100(385) | -200.0~630.0(-328.0~1166.0) | 0.2 | 0.4 | 0.4 | 0.05~0.4 |
| Pt100(385) JIS | -200.0~800.0(-328.0~1472.0) | 0.3 | 0.4 | 0.4 | 0.1~3.0 |



- Standard Accessories:**
- Dimension:**

Test lead, Hostler, Manual
190(H)x89(W)x42(D)mm

Contact Us
R.P. SINGH -7840088951
Email-cesindia1@gmail.com, cesindia@ymail.com
<http://www.cesindia.co.in>

Purifying your tomorrow